

# Container-Specification

All data is variable, depending on the intrinsic specificity and without warranty.



Standard-Container			Hi-Cube Container		
	20'	40'		40'	
Inside dimensions (L x W x H) in m	5.90 x 2.35 x 2.39	12.02 x 2.35 x 2.39	Inside dimensions (L x W x H) in m		12.02 x 2.35 x 2.69
Door opening (W x H) in m	2.33 x 2.29	2.33 x 2.29	Door opening (W x H) in m		2.33 x 2.59
Roof opening (L x W)			Roof opening (L x W)		
Tara in kg	2,000 - 2,400	3,550 - 4,000	Tara in kg		3,880 - 4,000
Volume in cbm	33.8	67.7	Volume in cbm		76.3
Loading capacity in kg	28,000	26,000 - 28,000	Loading capacity in kg		28,000

Refeer-Container			Open Top-Container		
	20'	40'		20'	40'
Inside dimensions (L x W x H) in m	5.54 x 2.35 x 2.39	11.56 x 2.26 x 2.22	Inside dimensions (L x W x H) in m	5.90 x 2.35 x 2.39	12.02 x 2.35 x 2.36
Door opening (W x H) in m	2.33 x 2.29	2.28 x 2.20	Door opening (W x H) in m	2.33 x 2.27	2.33 x 2.27
Roof opening (L x W)			Roof opening (L x W)	5.43 x 2.23	11.57 x 2.21
Tara in kg	2,850 - 3,500	4,500 - 5,400	Tara in kg	2,000 - 2,400	3,350 - 4,000
Volume in cbm	33.2	58.7	Volume in cbm	33.2	66.0
Loading capacity in kg	21,000 - 27,000	25,900	Loading capacity in kg	18,000 - 28,000	26,000

Flatrack			Collapsible Flatrack		
	20'	40'		40'	
Inside dimensions (L x W x H) in m	5.62 x 2.44 x 2.24	11.80 x 2.44 x 2.04	Inside dimensions (L x W x H) in m		11.80 x 2.44 x 2.04
Door opening (W x H) in m			Door opening (W x H) in m		
Roof opening (L x W)			Roof opening (L x W)		
Tara in kg	2,380 - 2,500	4,200 - 4,900	Tara in kg		4,200 - 4,900
Volume in cbm			Volume in cbm		
Loading capacity in kg	17,000 - 28,000	40,100	Loading capacity in kg		40,100